UL Online Certifications Directory

QUYX.E216851 Process Control Equipment, Electrical

Page Bottom

Process Control Equipment, Electrical

See General Information for Process Control Equipment, Electrical

GEFRAN SPA VIA SEBINA 74 25050 PROVAGLIO D'ISEO, BRESCIA ITALY E216851

Analog and digital solid state set point temperature controllers, Models 1600 or 1800, may be followed by P or V, followed by numbers and/or letters.

Model 40TB followed by 01, 05, 10, 15 or 24, followed by RRR, followed by 0, 1 or 2, followed by 0 or 1, followed by 0, 1, 2 or 3, followed by A-Z, followed by 0-9, followed by 0-9 or by 000.

Model 600 or 600-1 followed by R, followed by R, D or T, followed by 0, R, D, C, W, H or N, followed by 0, 2 or R, followed by 0 or 1; Model 40T followed by 48, may be followed by 3 or 4, followed by 00, 01, 15 or 24, followed by R, RD or T0, followed by 0 or R, followed by 0, 1, 2 or 3, followed by 0 or 1; Model 4T, followed by 48, may be followed by 3 or 4, followed by 00, 01, 15 or 24, followed by 0 or 1.

Model 4A followed by 96, followed by 3 or 4, followed by 0 or 1; Model 40A followed by 96, followed by 3 or 4, followed by RR, RD or T0, followed by 0 or R, followed by 0, 1, 2, or 3, followed by 0 or 1; Model 4B followed by 96, followed by 3 or 4, followed by 0 or 1; Model 40B followed by 96, followed by 96, followed by 01, 05, 10, 15 or 24, followed by 0 or 1; Model 40B followed by 96, followed by 0 or 1; Model 40F followed by 96, followed by 0 or 1; Model 4T followed by 3 or 4, followed by 00, 01, 15 or 24, followed by 00, 01, 15 or 24, followed by 00, 01, 15 or 24, followed by 0, 1, 2 or 3, followed by 0 or 1; Model 40T followed by 96, followed by 3 or 4, followed by 0, 00, 01, 15 or 24, followed by 0, 00, 01, 15 or 24, followed by 0, 00, 01, 0

Model 2400 followed by 0 or 1, followed by 0 or W, followed by 2R, 2D, 4R or 4D, followed by 0, 2, 3 or P, followed by 0 or 1, may be followed by Y, XX where Y may be 0 or a character between A and Z and XX a number between 00 and 99. Model 2500 followed by 0 or 1, followed by 0 or 1,

Model 2400 followed by 0 or 1, followed by 0 or W, followed by 2R, 2D, 4R or 4D, followed by 0, 2, 3 or P, followed by 0 or 1, may be followed by Y, XX where Y may be 0 or a character between A and Z and XX a number between 00 and 99.

Model 2500 followed by 0 or 1, followed by 0 or 1, followed by 0 or 1, followed by 0 or W, followed by 0 2, 3 or P followed by 0 or 1, may be followed by Y, XX where Y may be 0 or a character between A and Z and XX a number between 00 and 99.

Model 400/401, followed by R or D, followed by R or D may be followed by R, D or H, followed by 0 or 1.

Last Updated on 2006-09-26

Questions?

Notice of Disclaimer

Page Top

Copyright © 2006 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/showpage.html?nam... 06/10/2006

An independent organization working for a safer world with integrity, precision and knowledge.

